

Dehumidifiers



FRIEDRICH
1 8 8 3

25 | 50 | 70 Pints/hr.

Eliminate excess humidity and moisture



Displays room temperature and humidity %.



FEATURES

Comfort & Convenience:

- Top-mount digital touch controls display room temperature & relative humidity level
- Set humidity level from 30% to 90% RH
- Low temperature operation to 41°F
- Removable condensate bucket with handle
- Washable, slide-out filter
- 24 hr. ON/OFF timer
- 2-speed fan
- Automatic defrost cycle
- Auto-restart
- Casters for easy mobility
- 6 ft. power cord

Up to 3 Drainage Options:

- All models come with removable condensate bucket (up to 16 pts.) and continuous drainage outlet
- D50 and D70 also have built-in drain pump that can pump condensation vertically or horizontally up to a combined distance of 15 feet

Energy Efficiency:

- All ENERGY STAR® models
- Fan cycles off with the compressor

Sleek, Clean Modern Design


- Non-louvered front panel has a clean, stylish appearance that doesn't accumulate unsightly dust, pet hair and other household debris.

Dehumidifier Sizing Guide

Dehumidifier capacity is usually measured in pints per 24 hours and is determined by two factors:

The size of the space that needs to be dehumidified, and **the conditions that exist in the space** before dehumidification. Use the chart below to estimate the capacity you are looking for.

Room Conditions	Small to mid-size space	Mid-size to large space
	100 - 1,000 sq. ft.	1,000 - 2,000 sq. ft.
Damp Area feels damp and has a musty odor only in humid weather	D25 (25 pint)	D50 (50 pint)
Very Damp Area always feels damp & has a musty odor & may exhibit damp spots on walls & floors	D50 (50 pint)	D50 (50 pint)
Wet Area always feels and smells wet and the walls & floors sweat or seepage is present	D50 (50 pint)	D70 (70 pint)
Extremely Wet Area has wet floors or exhibits its standing water	D50 (50 pint)	D70 (70 pint)

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA)	Wall Outlet Appearance	Power Cord Length
All models	125V-15A	5-15P		6 FT.

SPECIFICATIONS

Model Number	D25BNP	D50BP	D70BP
ENERGY STAR®	Yes	Yes	Yes
Dehumidification Capacity* (Pints/24 hrs)	25	50	70
Built-in Drain Pump	No	Yes	Yes
Control	Digital	Digital	Digital
Power	115V/60HZ	115V/60HZ	115V/60HZ
Current (Amps)	4.5	5.9	7.7
Watts	240	533	746
Energy Factor (EF), L/kWh**	1.85	1.85	1.85
Compressor Type	Rotary	Rotary	Rotary
Refrigerant Type/Charge amount (Oz)	R-134a / 4.9 Oz	R-410A / 8.5 Oz	R-410A / 11.0 Oz
Operating Temperature Range	41°F- 95°F	41°F- 95°F	41°F- 95°F
Bucket Capacity (Pints)	11.5 approximate	16.2 approximate	16.2 approximate
Easy Roll Casters	Yes-included	Yes-built in	Yes-built in
Dimensions (WxHxD)	13 1/4"W x 21 1/2"H x 9 1/2"D	15"W x 23 1/4"H x 12"D	
Net Weight	32 lbs.	39 lbs.	47 lbs.
Shipping Weight	34 lbs.	44 lbs.	52 lbs.
Carton Dimensions (WxHxD)	15"W x 20 3/4"H x 11 1/2"D	16 1/4"W x 24 3/4"H x 13 3/4"D	



Built-in drain pump in models D50BP and D70BP.



*The rating is expressed in pints per 24 hour period at 80° F and 60% relative humidity. Dehumidifiers are tested using the ANSI/AHAM DH-1 standard.

**Energy Factor: The energy efficiency of dehumidifiers is measured by its energy factor, in liters of water removed per kilowatt-hour (kWh) of energy consumed or L/kWh. In general, a higher energy factor means a more efficient dehumidifier.

As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® models meet the ENERGY STAR® guidelines for energy efficiency. One year limited warranty on parts and labor; five years on the sealed refrigeration system.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.



Friedrich Air Conditioning Co. | 10001 Reunion Place, Suite 500 | San Antonio, TX 78216 | 877.599.5665 | www.friedrich.com